

Vertical Platform Lift Premier



Vertical Platform Lift Premier is Innovate's newest range. Developed with a focus on design and engineering expertise, the result is a new generation of modern state-of-the-art platform lifts.

A combination of the latest technology, aesthetic elegance, new materials, attractive pricing and a choice of options makes the Premier range the perfect accessibility solution for all types of buildings.

The standard model offers a broad range of alternative materials and colours. Supplied with a 1.1 m high vertical fascia with integrated control panel, and ready made with steel shaft panels or toughened and laminated safety glass for a fast and efficient site installation.

Alternatively the deluxe model has a 2.2 m high vertical fascia with integrated control panel, is supplied with an overhead light fitting, glass mirror and also offers a range of finishes.



Vertical Platform Lift Premier

TRAVEL UP TO 13 M

CARRY UP TO 400 KG OR 5 PEOPLE

SUITABLE FOR WHEELCHAIRS

INTERNAL OR EXTERNAL USE

PERFECT SOLUTION



OPTIONAL EXTRAS

- Battery lowering device
- Automatic lighting system
- Automatic door openers
- Voice annunciation
- Arrival bell
- IR control
- Telephone (wall telephone, safeline etc)
- Locking alternatives (smartcard, school lock system etc)
- Fold down seat
- Elbow contact
- Kit for external installation
- Control panel, hand rail and upper sensitive safety edge are available in optional surface coatings to resemble birch, beech, alder-tree and white marble


PRODUCT FEATURES

- Sensitive safety edge
- New control system enables smartcard use
- Natural anodised aluminium control panel with: large vandal resistant easy-to-use tactile push buttons; emergency light; stop button; clear, visible, easy-to-read instructions
- Softly moulded hand rail in natural anodised aluminium for a firm and comfortable grip
- Finished in RAL 9003 as standard but can be painted in any optional RAL colour
- Hidden screws provide a smooth surface finish



TECHNICAL SPECIFICATIONS for the Vertical Platform Lift Premier

Location	Internal or external
Travel	Up to 13 m (max 6 landings)
Rated Load	400 kg
Rated Speed	0.15 m/s
Platform Size	1500 x 1000 / 1500 x 1100 (length x width)
Footprint	1600 x 1400 / 1600 x 1500 (length x width)
Shaft	Steel panels Pre-painted in Off-white RAL 9003
Door configuration	Single entry, open through, adjacent
Doors	Single hinged doors or gates Steel door fronts pre-painted in off-white RAL 9003 Steel door fronts made in natural Anodised aluminium
Door dimensions	2000 x 900 mm
Gate dimensions	1100 x 900 mm
Control system	Micro computer based control system
Power supply	400 V AC, 3-phase, 50/60 Hz 16 amp starting current Soft start and stop as option (220 - 240 V 1-phase frequency converter) (230 - 400 V 3-phase frequency converter)
Motor power	2.2 Kw
Fault alarm	A potential free contact can be connected to central alarm units, receptions etc



FOR FURTHER INFORMATION

For professional advice, a quotation or further details on any of our lifting systems please contact us at:

Innovate Lifting Systems Ltd
The Southborough Centre
Warehouse No.1
Draper Street
Southborough
Tunbridge Wells
Kent TN4 0PG
T: 01892 557530
F: 01892 557531
E: info@innovatelifts.com
W: www.innovatelifts.com



Vertical Platform Lift Premier