

innovate  
lifts



**Innovate300**  
Open Platform Lift

## Innovate300 Open Platform Lift



**Innovate 300** is an Open Platform Lift, also known as Wheelchair Lift, which provides internal or external vertical travel up to 3 meters. Our Open Platform Lift can accommodate changes in level from 600 mm up to 3000 mm in commercial and domestic environments and is appropriate alternative solution to a fully enclosed platform lift.

**Innovate 300** is specifically designed for applications with little or no alterations to existing buildings. The open type design offers an aesthetically pleasing solution

with brushed stainless steel finish as option. The lift provides a safe and easy way to gain access to a property where stairs would otherwise prevent wheelchair access.

It is designed to give customers choice and flexibility.

**Innovate 300** Wheelchair Lift is a space saving and cost effective way to provide access for everyone to your home or workplace.




## Features

- Modern lightweight design
- Stainless steel construction as option
- Low space requirements
- High level of security
- Silent operation
- Simple to use
- No pit required
- Simple to install and easy to service
- Overall low maintenance and running costs

### Top floor gate


Stainless steel finish for external use  
850 x 1100 mm (Manual opening) (Left)



### Bottom floor gate

850 x 1100 mm (Manual opening) (Left)

## BELLOWS UNDER THE PLATFORM



### 3 lifting heights:

from 2010 to 3000 mm,  
pit = 350 mm,  
1500 euros.

from 1010 to 2000 mm,  
pit = 260 mm,  
1200 euros.

from 600 to 1000 mm,  
pit = 170 mm,  
1100 euros.

Fixations: on ground floor, at the four corners of the below, and at the platform, fixations will be provide.

### Platform size possible:

1100 x 1400 mm  
(shaft 1300 x 1760 mm).  
Gate opening = 950 mm.



# innovate lifts

## Other Options:

### Platform

900 x 1600mm  
1000 x 1600mm

### Gate

Automatic upper gate  
Automatic lower gate

### Control

Configurable control side  
Dual control on the platform  
Auto slider on the platform  
Remote control  
Brake on the control

### Safety

Battery emergency lowering device

### Finish

Painted in any RAL colour  
Brushed Stainless Steel



|                     |  |
|---------------------|--|
| User group          | Ambulant and wheelchair users                                  |
| Suitability         | For internal or external use                                   |
| Travel              | From 600 mm up to 3000 mm                                      |
| Number of steps     | 2  |
| Maximum capacity    | 400 kg   |
| Platform size       | 1000 x 1400 mm (standard)                                      |
| External dimensions | 1300 x 1770 mm (standard)                                      |
| Gate                | 950 x 1000 mm (standard)<br>with auto closers                  |
| Cabin height        | 1800 mm  |
| Drive type          | Belt   |
| Power               | 230-240 V, 1 phase, 16A<br>380-400 V, 3 phase, 10A, 50 Hz      |
| Lighting            | Controls illuminated   |
| Safety edge         | Safety edge-under platform-proximity sensors                   |
| Handrail            | Integrated to lift cabin (on both sides)                       |
| Machine room        | Integral to guide rails  |
| Floor               | Anti-slip rubber (Anti-slip-diamond plate for outdoor version) |
| Finish              | RAL 9006 (Anodized aluminium)                                  |



innovate  
lifts

Innovate Lifts Ltd  
Office 1, The Lakeside Centre,  
Eastleigh, Hampshire SO50 5PE

Tel: 01892 557530

Tel: 02382 516739

[www.innovatelifts.com](http://www.innovatelifts.com)  
[info@innovatelifts.com](mailto:info@innovatelifts.com)